

1 projections containing interior spaces, but do not include bay windows. This term  
 2 includes all structures which meet the above requirements except the size requirements  
 3 and with respect to which the manufacturer voluntarily files a certification pursuant to  
 4 § 3282.13 and complies with the standards set forth in Part 3280.

5 Note: for mobile homes built prior to June 15, 1976, a label certifying compliance to  
 6 the standard for mobile home, NFPA 501, ANSI 119.1, in effect at the time of  
 7 manufacture is required. For the purpose of these provisions, a mobile home shall be  
 8 considered a manufactured home.”

- 9 (7) Table R301.2(1) is amended by adding the following design values: “Ground snow  
 10 load - 30 psf; Wind - 90 mph; Topographic effects – no; Special wind region – no;  
 11 Wind-born debris zone – no; Seismic design category - b; Weathering - severe; Frost  
 12 line depth - 30 inches (762 mm); Termite - moderate to heavy; Winter design temp -  
 13 13° F.; Ice barrier underlayment required - no; Flood hazards - July 16, 1981 and  
 14 January 7, 2000; Air freezing index - 554; Mean annual temp - 31°F; LATITUDE -  
 15 39° N; WINTER HEATING - 99% 70  ~~COOLING~~ 1% 95 ;  
 16 ALTITUDE CORRECTION FACTOR - 1.0; INTERIOR DESIGN TEMPERATURE  
 17 - 10  ~~DESIGN TEMPERATURE COOLING~~ HEATING  
 18 DIFFERENCE - 60  ~~WIND VELOCITY~~ HEATING  
 19 COOLING - 7.0; COINCIDENT WET BULB - 77  ~~WINTER RANGE~~  
 20 HUMIDITY - 30%; SUMMER HUMIDITY - 50%.”.

- 21 (8) Table R302.1(1) is amended by adding the following line at the bottom of the table:  
 22

All portions of attached decks and open roof covered decks. Open roof covered decks may have a maximum opaque wall surface area of 50%	Not allowed	N/A	< 2 feet
--	-------------	-----	----------

- 23  
 24 (9) Table R302.1(2) is amended by adding the following line at the bottom of the table: